


PRODUCT DESCRIPTION

Dymonic® FC is a high-performance, fast-curing, single-component, low modulus, hybrid sealant formulated with proprietary silane end-capped polymer technology.

DYMONIC FC STANDARD COLORS



APPLICABLE STANDARDS

ASTM C 920 Type S, Grade NS, Class 35, Use NT, M, A and O; ASTM C 1248; CAN/CGSB-19.13-M87; U.S. Federal Specification TT-

Colors shown are approximate and may not reflect the shade precisely. Different lighting conditions can influence color appearance, for truer color please view in daylight. Standard colors vary by package sizes. Custom colors and alternate packaging available. Contact Tremco Customer Service for more information.

Tremco Commercial Sealants & Waterproofing | 3735 Green Road | Beachwood, OH 44122 | US: 800.852.9068 | CAN: 800.363.3213 | tremcosealants.com

Tremco Construction Products Group (CPG) brings together Tremco CPG Inc. and its Dryvit and Nudura brands; Willseal; Prebuck LLC; Tremco Barrier Solutions, Inc.; Weatherproofing Technologies, Inc. and its Pure Air Control Services and Canam Building Envelope Specialists offerings; and Weatherproofing Technologies Canada, Inc.

Use of the ® symbol indicates registration with the US Patent & Trademark Office and the Canadian Intellectual Property Office.
© Tremco CPG Inc. 2022